150-H

Reduced budgets and less frequent mowing cycles mean that the local authorities require a machine that will cut and mulch lush grass without untidy swathing, as with a rotary mower. The Wessex **FRX-150/FRX-150-H** (hydraulic version) out-front flail mowers will do just that!



KEY FEATURES & BENEFITS

- **1 AERODYNAMIC FLAILS** Minimum power consumption.
- **FULL WIDTH ANTI-SCALP ROLLER** No unsightly scalping.
- **3 INTEGRAL ROLLER BEARINGS** Protected for long service life.
- 4 SIMPLE AND POSITIVE HEIGHT ADJUSTMENT Ease of operation.
- **5 PUNCTURE PROOF TYRES** Low maintenance.
- **TWIN DRIVE BELT TRANSMISSION** Handles dense vegetation.
- FULLY GUARDED TO HSE SPECIFICATIONS
 Meets local authority requirements.
- **8 CONTIFLOW DECK DESIGN** Low profile deck design follows the path of the flails at a constant distance increasing the suction effect and improving mulching efficiency.
- **9 FLOATING LINKAGE** Excellent ground contour following and a generous lift height which is ideal for curb clearance and trailer ramps etc.
- **10 WIDE OUTLET** Maximum performance in long grass.
- **11 HARDENED STEEL STONE GUARDS** Safety in public areas.
- 12 RIGHT ANGLE DRIVE GEARBOX OR HYDRAULIC MOTOR Smooth and quiet operation.
- **13 ROTOR BEARING GUARDS** Protected for long service life.
- **14** ADJUSTABLE SIDE SKIDS WITH **REMOVABLE WEAR-SHOES** Low maintenance costs.

SPECIFICATIONS

	FRX-150	FRX-150
Cutting width	1.5m	1.5m
Overall width	1.73m	1.73m
Weight	220kg	212kg
Cutting height range	25-100mm	25-100mm
No. of flails	34	34

